
SAFETY AND PROPER USAGE

SAFE1 TAIND PROFER OSAGE To ensure safe and enduring performance of this product, you must comply strictly with the instructions enclosed herein. Non-compliance with instructions or improper handling of the product will void your warranty! Usage of this product in conditions not specified in this manual or in contrary to the instructions hereby provided is considered IMPROPER. The manufacturer will not be held liable for any damages resulting from improper use of the product.

SAFETY & WARNING INSTRUCTIONS

SAFETY & WARNING INSTRUCTIONS
- Observe valid and generally accepted safety rules when planning, installing and using this product.
- Take proper measures to prevent unintentional operation of the product or damage to it.
- Do not attempt to disassemble this product or lines in the system while they are under pressure.
- Always depressurize the compressed air system before working on the system.
It is important that personnel use safe working practices and observe all regulations and legal requirements for safety
when operating this product. When handling, operating or carrying out maintenance on this product, personnel must
employ safe engineering practices and observe all local health & safety requirements & regulations. International users
refer to regulations that prevail within the country of installation. Most accidents, which occur during the operation and
maintenance of machinery, are the result of failure to observe basic safety rules or precautions. An accident cansing injury or death. The manufacturer cannot anticipate every possible
circumstance, which may represent a potential hazard. The WARNINGS in this manual cover the most common potential
hazards and are therefore not all-inclusive. If the user employs and poreating or easile unsafe angured in a decident can be
damaged or made unsafe and that there is no risk to persons or property. **VEVER CHANGE ORIGINAL COMPONENTS WITH ALTERNATIVES** NEVER CHANGE ORIGINAL COMPONENTS WITH ALTERNATIVES

MARNING This product can expose you to chemicals including lead, which is known to the State of California to cause cancer and/or birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov













COIL SEALING SET



INSTALLATION INSTRUCTIONS

Before installing this product, make sure it complies with your request and that it suits your application!

1. Unpack the unit and visually inspect for any transport damage incurred after leaving our factory.

2. Take the solenoid valve on which you would like to install the IP coil sealing set. The solenoid valve may look different than the one illustrated below.

3. Remove the top nut using a 14mm wrench.

4. Remove the coil + washer.

5. Replace the black O-ring with the brown valve gasket supplied in the IP coil sealing set.

6. Place the coil and the IP top nut + top nut gasket and hand-tighten them firmly.

7. Your solenoid valve with IP coil sealing set is ready to be installed.